

INTIMIDATOR™ 19XP

19" Capacity Hand-Fed Chipper

The Intimidator 19XP is a powerful drum-style chipper that can easily handle big limbs, forked material and whole trees. It's an extremely versatile chipper, configurable as both a single-axle unit, or a tandem-axle machine for heavy-duty applications. With its solid steel welded construction, proven feed system, durable components, and chip throwing technologies, the Intimidator 19XP is a favorite for tree services needing a high-capacity chipper that's easy to maneuver.

DURABLE AND POWERFUL.

- Aggressive whole tree chipping power in a maneuverable package
- Large 37" diameter reinforced chipping drum
- Wide 20-1/2" x 26 1/4" opening for processing large limbs and whole trees



Chip Limby Material With Limited Preparation

The Intimidator 19XP easily handles limby material and forked branches because of the chipper's large throat opening and Bandit's powerful Slide Box Feed System. This system features powerful dual horizontal feed rollers 20" wide by 10-5/8" in diameter, powered by 63.9 CID hydraulic motors. The feed rollers are positioned within inches of the chipping knives, effectively controlling even the wildest trees and branches. This reduces trimming time and labor costs while increasing production.

Excels at Chipping Large Diameter Materials

The large 37" diameter drum allows much of the material to be chipped on the bottom half of the drum, with the grain of the wood like a disc-style chipper. Large limbs and whole trees are chipped using less energy and with less vibration, maximizing fuel economy and reducing maintenance. The large chipper opening and sloped infeed system makes it easy to feed large logs, and whole trees into the chipper. And with aggressive engine options over 200 horsepower, the Intimidator 19XP has plenty of power to tackle big projects.

Slide Box Feed System

This unique system allows the top feed wheel to move straight up and down with the flow and diameter of material passing through the feed system into the chipper. The slide box feed system provides direct down pressure for crushing material. Included within the slide box, is the patented spring tensioning system along with the hydraulic lift cylinder providing additional down pressure for unmatched pulling and compressing power making the unit easier to feed and more productive.

Significantly Less Maintenance

The Intimidator 19XP has a heavy, reinforced drum with internal baffles. The chipper drum and shaft should last the lifetime of the chipper and are backed by a five-year GUTS warranty. Rugged construction and heavy-duty components throughout the Intimidator 19XP help ensure long life and trouble-free performance. We realize what it costs when a chipper is down, and though we can't eliminate all downtime, we do our best to minimize it.

Higher Quality Chips Per Load

The Intimidator 19XP throws chips with more force due to the pocket design, the larger drum diameter, smooth transition, smooth discharges and the patented Power Slot. This means more chips per load and fewer trips to the dump site. It also means chips from a Bandit chipper have better uniformity compared to rival machines, commanding higher prices when sold and making them easier to dispose of.



Bandit INDUSTRIES, INC.

6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178

FIND US ONLINE     WWW.BANDITCHIPPERS.COM

Intimidator™ 19XP

19" capacity drum-style chipper



Safety Features

- **Rope/Line Shear Device (standard)**
Provides an improved chance that rope or lines inadvertently entering the chipper may be cut.
- **Last Chance Cables (standard)**
Stops/reverses the feed wheel when pulled in case of an emergency.
- **Operator Safety Control Bar (standard)**
Wraps around three sides of the infeed chute and controls the direction of the feed wheels.
- **Wood Pusher Paddle (standard)**
Used to feed small wood debris into the chipper.
- **Chipper Hood Pin w/Padlock (standard)**
Prevents unauthorized access to the disc or drum.
- **Chipper Hood Engine Disable Plug (standard)**
Prevents engine from being started without the hood pin in place.
- **Feed Wheel Engage (option)**
Requires operators to control feed wheel operation via foot pedal.
- **Hydraulic Bottom Bump Bar (option)**
Stops feed wheels via mechanical connection when bumped, diverting hydraulic power away from the feed wheels.

The Bandit Backbone™ Support

The Bandit Backbone is Bandit's commitment to customer service and support. It's always been a cornerstone of Bandit's philosophy, and today that backbone is stronger than ever. If you own a Bandit hand-fed chipper—regardless the age, hours, or warranty status—the Bandit Backbone is here to support you.



Popular Options



Wide Feed Wheel

Optional 32" wide feed wheel.



Self-Propelled

Available with a track undercarriage, the Intimidator 19XP can be taken directly to the trees.



Hydraulic Winch

This useful option enables the operator to pull large material to the chipper with ease.

Intimidator™ 19XP Specifications

ENGINES

TOWABLE:

- GM 165 HP Gas
- CAT or Perkins 147 HP Tier 4 Final
- CAT or Perkins 174 HP Tier 4 Final
- CAT or Perkins 225 HP Tier 4 Final
- John Deere 200 HP Tier 4 Final

TIER 3 DIESEL ENGINE OPTIONS (EXPORT ONLY)

- CAT 142 HP Tier 3
- CAT 173.7 HP Tier 3
- CAT 213 HP Tier 3
- John Deere 173 HP Tier 3

TRACK:

- CAT 225 HP Tier 4 Final

TIER 3 DIESEL ENGINE OPTIONS (EXPORT ONLY)

- CAT 142 HP Tier 3
- CAT 173.7 HP Tier 3
- CAT 213 HP Tier 3
- John Deere 173 HP Tier 3
- CAT 250 HP Tier 3

UNDERCARRIAGES

TOWABLE:

AXLE - Single 12,000 lb. electric brake
TIRES - 235/75R 17.5" tires mounted on 8-bolt heavy-duty gray rims

TRACK:

RUBBER TRACK - 305 DCR rubber track undercarriage
STEEL TRACK - Caterpillar 305CR (400MM, triple grouser)

MEASUREMENTS:

| | TOWABLE: | TRACK: |
|-----------------------------------|------------|------------|
| Length: (Infeed Closed) | 17' 1" | 13' 9" |
| Length: (Infeed Open) | 19' | 16' |
| Width: | 7' 5" | 8' 6" |
| Height: | 9' 5" | 10' |
| Weight: | 10,800 lbs | 14,000 lbs |
| Fuel Tank: | 40 gal | 50 gal |
| Hyd. Tank: | 30 gal | 50 gal |

OTHER SPECIFICATIONS:

| | |
|--------------------------------|---|
| Capacity: | 19" |
| Throat Opening: | 20-1/2" x 26-1/4" |
| Drum: | 37" diameter x 22" wide (3/8" Thick) |
| RPM: | 1,080 |
| Feed System: | Slide Box System |
| Adjustable Springs: | 2 - 27" long |
| Horizontal feed wheels: | 20" wide x 10-5/8" diameter |
| Displacement (CID): | 63.9 |
| Hydraulic Motors: | 2 |
| Discharge: | Hand Crank Swivel |
| Deflector: | 3-Position Manual |
| Hitch: | 3 Position, 2-1/2" Pintle |
| Frame: | 3/16" x 2" x 6" main frame rectangular tubing with a 3/8" x 3" x 6" tongue |
| Fenders: | Preformed 12 gauge aluminum tread brite fenders with mud shields |
| Tongue Jack: | 8,000 pound "Bulldog" tongue jack, adjustable for height with 15" travel capacity and stationary foot pad |

Standard & Custom Colors Available

Choose from six standard colors, or select a custom color to match your fleet.

| | | | | | |
|-----------------|------------------|---------------|-------|-------|-------|
| | | | | | |
| ALERT ORANGE | BANDIT YELLOW | CAT YELLOW | GREEN | BLACK | WHITE |