

PERFORMANCE OF A LIFETIME

Bandit chippers have proven over time to be the best decision you can make for a long-term investment in a brush chipper. Like all Bandit models, the 15XP is engineered for maximum performance, built to have the longest lifespan on the market, and equipped with features that increase operator productivity over time.

SUPER CHARGE YOUR PRODUCTION

Bandit chippers are easier to feed, so you'll be more productive during the day. Bandit's unique slide box feed system and powerful dual horizontal feed rollers, which are 18-3/4" wide by 10-5/8" in diameter and powered by a pair of 32.3 CID hydraulic motors, crush and compress material, easily guiding it to the powerful drum.

MAXIMIZE YOUR UPTIME

The most common maintenance items are easy to access on Bandit chippers. Bolt-in knives are easy to access and change through the chipper hood. And all service areas are easy to access, including all grease points, so daily maintenance is simple and quick.

REDUCE YOUR FUEL COSTS

The 15XP's drum turns at a lower RPM, generating greater torque, and the synchronized feed system never underfeeds or forces material against the drum. The result is a more efficiently fed chipper that reduces idle time and translates to fuel savings up to 30 percent.



6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178
FIND US ONLINE

| WWW.BANDITCHIPPERS.COM

Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments

Al specifications, dimensions and options are subject to change without notice, and were current at the time of printing, Dimensions may very, depending on options and engines selected. Bandit Industries, Inc. reserves the right to change designs, specifications and options without prior notice. © 2020 Bandit Industries, Inc. Al Rights Reserve

SPECIFICATIONS

MEASUREMENTS	TOWABLE		TRACK	
Length:	17' 8"	538.5 cm	14' 6"	442 cm
Width:	6' 6"	198.1 cm	8' 1"	246.4 cm
Height:	8' 6"	259.1 cm	9' 3"	281.9 cm
Weight:	8,000 lbs.	3,629 kg	11,500 lbs.	5,216 kg
Engines:	120-174 HP (89-130 kW)		139-174 HP (104-130 kW)	
Fuel Tank:	25 gal.	94.6 L	50 gal.	189.3 L
Hydraulic Tank:	12 gal.	45.4 L	50 gal.	189.3 L

UNDERCARRIAGES

Towable: Single 10,000 lb. (4,536kg) axle with (2) ST215/75R 17.5" (44.5 cm) tires mounted on 8-bolt heavy-duty gray rims

Track: Rugged CAT 305 rubber track undercarriage

Standard & Custom Colors Available

Choose from six standard colors, or select a custom color to match your fleet.











Black White

DIMENSIONS Capacity: 15" 38.1 cm Opening: 17.75" high x 18.5" wide 45 cm high x 47 cm wide Drum: 37" dia. x 18.75" wide 94 cm dia. x 47.6 cm wide RPM: Approximately 1,080 RPM Hitch: 2-½" pintle hitch

Discharge: Height-adjustable, 360° manual swivel with 12" (30.5 cm) adjustable chip deflector

Feed System: Slide box feed system with (2) 21" (53 cm) adjustable down pressure springs, (2) 10-5/8" diameter x 18-3/4" wide feed wheels (27 cm x 47.63 cm) powered by (2) 32.3 CID hydraulic motors

Frame: Mainframe is constructed of 3/16" x 2" x 6" rectangular tubing (0.48 x 5.1 x 15.24 cm)



COMMITTED TO QUALITY & SERVICE

The Bandit Backbone™ Support

The Bandit Backbone is Bandit's commitment to customer service and support. It's always been a cornerstone of Bandit's philosophy, and today that backbone is stronger than ever. If you own a Bandit hand-fed chipper –regardless the age, hours, or warranty status – the Bandit Backbone is here to support you.

We Are Here to Support You

There are nearly 200 dealer locations in the US and over 60 international dealers to support you. They are factory trained. Plus we have an experienced parts and service department supporting you and our dealers.



INTIMIDATOR™ 15XP FEATURES

- Rope/Line Shear Device (standard)
 Provides an improved chance that rope or lines inadvertently entering the chipper may be cut
- Last Chance Cables (standard)
 Stops/reverses the feed wheel when pulled in case of an emergency
- Operator Safety Control Bar (standard)
 Wraps around 3 sides of the infeed chute & controls the direction of feed wheels
- Wood Pusher Paddle (standard)
 Used to feed small wood debris into the chipper
- Chipper Hood Pin w/Padlock (standard)
 Prevents unauthorized access to the disc or drum
- Chipper Hood Engine Disable Plug (standard)
 Prevents engine from being started without the hood pin in place
- Hydraulic Bottom Bump Bar (option)
 Stops feed wheels via mechanical connection when bumped, diverting hydraulic power away from the feed wheels



Bandit Offers a Complete Line of Tree Care Equipment: Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments